



Description

Our new PLASTOFUSED PRO is equipped with a LCD-display which shows the set temperature and the real temperature. We can reach higher temperatures by using a lower nitrogen volume as this is the key to be able to achieve a good bonding. With this we get the plastic faster up to its own melting flow index (MFI) which then makes it ideal for bonding. With the special designed flat welding strip we created a tool for a quick, simple and high quality plastic-repair.

Benefits

- Quick, economical & efficiently
- Highest standard of quality — Made in Germany
- Flexible results due to the nitrogen supply
- Ideal mixture of air pressure and temperature
- Incl. Trolley with one big tray
- Easy to handle
- High-quality main-housing
- Modern design
- Wide range of accessories
- Different Melting-Strips
- Different fields of application



Scope of delivery

- PLASTOFUSED-unit
- Hose package including handle and hot air nozzle
- PLASTOFUSED-Trolley with extension for nitrogen bottle
- Hose (Ø 6mm) with quick connection
- Special flat-nose-plier
- Plastic Scraper, 3-edged
- Pneumatic grinder incl. 2 grinding discs C.40
- Melting-Strips (PU 15 pcs.), black for Polypropylen (PP-EPDM)
- Melting-Strips (PU 15 pcs.), black for Acrylnitril-Butadien-Styrol (ABS)
- Robust cardboard packaging incl. inlay
- Manual

Technical data

Operating voltage	230 V~
Power	320 W / 1,49 A
Adjustable temperature	160...480 °C / 320...896 °F
Display	double-spaced LCD-display
Nozzle ø	5 mm
Hose package	2000 mm / removable
Protection class	IP 42
Manufacturer	KAMATEC
Made in	Germany
Supply	Nitrogen

Dimensions & Weight

L x W x H	140 cm x 248 cm x 169 cm
Weight	kg

For further questions please do not hesitate to contact us.

KAMATEC GmbH
Im Oberen Tal 31
74858 Aglasterhausen
GERMANY

Tel: +49 (0) 6262 / 92 605-0
Fax: +49 (0) 6262 / 92 605-29
Mail: info@kamatec.com
Web: www.kamatec.com